## AKSESS-PAVEMENT HYDRAULIC MANHOLE COVER

- Ductile iron
- Hydraulic manhole cover
- B 125 class
- New black varnish coating
- EN 124

### STABLE, QUIET AND STRONG

**Thanks to their perfect stability, AKSESS manhole covers ensure quiet, trouble-free use for pedestrians and residents alike.**

- 3-point non-rock system ensures the cover remains firmly seated in its frame
- Rigid and stable frames incorporating the LTS® system
- The underside of the wide seating pads located at each corner of the frame have a unique corrugated design that improves embedment and increases resistance to lateral shear by up to 5 times more than conventional designs

### APPEARANCE

**AKSESS is a range of attractive and functional manhole covers for pavement applications featuring:**

- A new dynamic non-skid surface pattern,
- A universal lifting point with integral usage indicator
- A specific diagram for the locked versions

### EASY OPERATION

**AKSESS, the fast and ergonomic solution for access to networks installed under pavements**

- Opens effortlessly and remains stable in the vertical position in its frame;
- Slides effortlessly for practical handling;
- The lifting point for non-locked AKSESS covers is ergonomic and designed for use with standard tools

### LOCKED AKSESS COVERS

### SECURITY AND THEFT DETERRENCE

The locked version of Aksess covers meets specific requirements for the prevention of theft, vandalism and intrusion

- Protection of appliances and equipment installed under pavements
- Deterrent against cover theft
- Locked AKSESS covers have a special opening that can only be operated using the AKSESS key, which operates the special 1/4-turn lock
- Guaranteed protection of your equipment.

## AKSESS-PAVEMENT HYDRAULIC MANHOLE COVER

**Specific AKSESS caps:**

- Protect the locking system against the ingress of debris
- Identify the type of network installed under the pavement

The AKSESS caps symbolise four of the most common services for which manholes are used:

- Wastewater
- Storm water
- Water meters
- Lighting/Traffic lights

*Each locked Aksess manhole cover is supplied with four identification caps.*

### STANDARD VERSION (NON LOCKED)

| Type | Reference | Dimensions mm | | | Mass kg |
|---|---|---|---|---|---|
| | | Outside of frame | Clear opening | Frame Height | |
| Aksess 300 | CBAK30HF | 310 x 310 | 220 | 37 | 8.2 |
| Aksess 400 | CBAK40HF | 410 x 410 | 300 | 37 | 12.8 |
| Aksess 450 | CBAK45HF | 460 x 460 | 350 | 38 | 15.3 |
| Aksess 500 | CBAK50HF | 510 x 510 | 400 | 38 | 18.2 |
| Aksess 550 | CBAK55HF | 550 x 580 | 450 | 38 | 22.0 |
| Aksess 550 x 700 | CBAK75HF | 560 x 710 | 450 x 600 | 38 | 32.0 |
| Aksess 600 | CBAK60HF | 610 x 610 | 500 | 38 | 29.4 |
| Aksess 700 | CBAK70HF | 720 x 720 | 600 | 38 | 38.8 |
| Aksess 800 | CBAK80HF | 820 x 820 | 700 | 41 | 52.7 |

### LOCKED VERSION

| Type | Reference | Dimensions mm | | | Mass kg |
|---|---|---|---|---|---|
| | | Outside of frame | Clear opening | Frame Height | |
| Aksess 300 | CBAK30HFX16 | 310 x 310 | 220 | 37 | 8.2 |
| Aksess 400 | CBAK40HFX16 | 410 x 410 | 300 | 37 | 12.8 |
| Aksess 450 | CBAK45HFX16 | 460 x 460 | 350 | 38 | 15.3 |
| Aksess 500 | CBAK50HFX16 | 510 x 510 | 400 | 38 | 18.2 |
| Aksess 550 | CBAK55HFX16 | 550 x 580 | 450 | 38 | 22.0 |
| Aksess 550 x 700 | CBAK75HFX16 | 560 x 710 | 450 x 600 | 38 | 32.0 |
| Aksess 600 | CBAK60HFX16 | 610 x 610 | 500 | 38 | 29.4 |
| Aksess 700 | CBAK70HFX16 | 720 x 720 | 600 | 38 | 38.8 |
| Aksess 800 | CBAK80HFX16 | 820 x 820 | 700 | 41 | 52.7 |